


- ALL EXTERNAL SURFACES SATIN FINISH.
- MAXIMUM OPERATING CONDITIONS:
  - PRESSURE: TUBESIDE 700 psi (48 bar) SHELLSIDE - 400 psi (28 bar)


  - TEMPERATURE: 800°F (425°C)
    PRESSURE FOR STEAM SERVICE: 125 psi (8.6 bar)
    FLUID TEMPERATURE DIFFERENCE: (Thot) AVE - (TCOLD) AVE <125°F (70°C)







ALSO AVAILABI	<u>E</u>





- #	TUBE	TUBE LENGTH		DIM A		DIM B		WEIGHT EMPTY		TRANSFER AREA	
	COUNT	in	mm	in	mm	in	mm	lb	kg	f†²	m²
- 01		10.00	254	16.00	406	7.38	187	11.20	5.08	6.51	0.60
- 02	253	15.00	381	21.00	533	12.38	314	13.60	6.17	9.96	0.93
- 03		20.00	508	26.00	660	17.38	441	16.10	7.30	13.41	1.25
- 05		10.00	254	16.00	406	7.38	187	9.59	4.35	2.83	0.26
- 06	55	15.00	381	21.00	533	12.38	314	12.31	5.58	4.33	0.40
- 07		20.00	508	26.00	660	17.38	441	15.04	6.82	5.83	0.54
- 08	253	25.00	635	31.00	787	22.38	568	18.96	8.60	16.86	1.57
- 09	255	30.00	762	36.00	914	27.38	695	21.47	9.74	20.31	1.89
- 10		10.00	254	16.00	406	7.38	187	11.20	5.08	9.38	0.87
- 11		15.00	381	21.00	533	12.38	314	13.55	6.15	14.36	1.33
- 12	365	20.00	508	26.00	660	17.38	441	15.90	7.21	19.34	1.80
- 13		25.00	635	31.00	787	22.38	568	18.26	8.28	24.31	2.26
- 14		30.00	762	36.00	914	27.38	695	20.31	9.21	29.29	2.72






## ALL DIMENSIONS ARE IN INCHES [mm]

## PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE SOLE PROPERTY OF EXERGY, LLC. ANY REPRODUCTION, DISCLOSURE, OR USE, IN PART OR AS A WHOLE, WITHOUT THE WRITTEN PERMISSION OF EXERGY, LLC IS PROHIBITED.

PRODUCT SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE, MANUFACTURER ASSUMES NO LIABILITY FOR MISUSE OR ABUSE OF PRODUCT. SPECIFIC WARRANTY INFORMATION IS AVAILABLE UPON REQUEST.

THIRD ANGLE **PROJECTION** 



320 ENDO BLVD. GARDEN CITY, NY 11530 USA (516)832-9300 www.exergyllc.com

## SHELL & TUBE HEAT EXCHANGER 73 SERIES **TUBE STUB**

MODEL NO.

00604 - #

DATE 9/23/2014

SCALE 1:4 SHEET

OF 1

MODEL NO.

00604 #